

Specifications

PCI-PDISO8



**MEASUREMENT
COMPUTING™**

Document Revision 1.3, May, 2006

© Copyright 2006, Measurement Computing Corporation

Specifications

Typical for 25°C unless otherwise specified.

Specifications in *italic text* are guaranteed by design.

Relay specifications

Table 1. Relay specifications

Number	8
Contact configuration	5 FORM C (SPDT) RELAY 0 through RELAY 4
	3 FORM A (SPST) RELAY 5 through RELAY 7
Contact rating	<i>6 A @ 120 VAC or 28 VDC resistive (see connector rating below)</i>
Contact resistance	100 milliohms max
Operate time	<i>20 milliseconds max</i>
Release time	<i>10 milliseconds max</i>
Vibration	<i>10 to 55 Hz (Dual amplitude 1.5 mm)</i>
Shock	<i>10 G (11 milliseconds)</i>
Dielectric isolation	<i>500 V (1 minute)</i>
Life expectancy	<i>10 million mechanical operations, min</i>
Power on RESET state	Not energized. NC in contact to Common.

Isolated inputs

Table 2. Isolated input specifications

Number	8
Isolation	<i>500 V</i>
Resistance	1.6 k Ohms min.
Voltage range	DC: 5 to 28 V (Not TTL compatible)
	AC: 5 to 28 V (50 to 1000 Hz)
Input 'High' level	>5V min (positive or negative input voltage - not TTL compatible)
Input 'Low' level	<2.5V max (positive or negative input voltage)
Response	w/o filter: 20 μ S
	w/filter: 5 mS
Filters	Time constant: 5 mS (200 Hz)
	Filter control: Software programmable at each input
	Power-up /reset: Filters off

Power consumption

Table 3. Power consumption specifications

+5 V Power	All relays off: 0.4 A typical
	All relays on: 1 A typical

Environmental

Table 4. Environmental specifications

Operating temperature range	0 to 70 °C
Storage temperature range	-40 to 100 °C
Humidity	0 to 90% non-condensing

Main connector and pin out

Table 5. Main connector specifications

I/O connector type	37-pin D connector
Compatible cable	C37FF-x, where x = length in feet C37FFS-x, where x =5 or 10 feet
Compatible accessory products (with the C37FFS-x and C37FF-x cables)	CIO-MINI37 SCB-37
Max current	5 A

Table 6. Connector pin out

Pin	Signal Name	Pin	Signal Name
1	Input 7A	20	Input 7B
2	Input 6A	21	Input 6B
3	Input 5A	22	Input 5B
4	Input 4A	23	Input 4B
5	Input 3A	24	Input 3B
6	Input 2A	25	Input 2B
7	Input 1A	26	Input 1B
8	Input 0A	27	Input 0B
9	Relay 7 (C)	28	Relay 7 (NO)
10	Relay 6 (C)	29	Relay 6 (NO)
11	Relay 5 (C)	30	Relay 5 (NO)
12	Relay 4 (NC)	31	Relay 4 (C)
13	Relay 4 (NO)	32	Relay 3 (NC)
14	Relay 3 (C)	33	Relay 3 (NO)
15	Relay 2 (NC)	34	Relay 2 (C)
16	Relay 2 (NO)	35	Relay 1 (NC)
17	Relay 1 (C)	36	Relay 1 (NO)
18	Relay 0 (NC)	37	Relay 0 (C)
19	Relay 0 (NO)		

Measurement Computing Corporation
10 Commerce Way
Suite 1008
Norton, Massachusetts 02766
(508) 946-5100
Fax: (508) 946-9500
E-mail: info@mccdaq.com
www.mccdaq.com